
PTFE PISTON SEAL JSPGO



Advantages:

- No stick-slip effect when starting for smooth operation
- Low friction and high wear resistance ensure long service life.
- Min. Static and dynamic friction coefficient ensure high speed
- Simple groove design, one-piece piston possible.
- Suitable for most hydraulic fluids
- Available for all cylinder diameter up to 500 mm

ITEM	OD	H
SPGO	30	3.2
SPGO	35	3.2
SPGO	40	3.2
SPGO	45	3.2
SPGO	28	4.2
SPGO	30	4.2
SPGO	32	4.2
SPGO	35	4.2
SPGO	40	4.2
SPGO	45	4.2
SPGO	50	4.2
SPGO	55	4.2
SPGO	60	4.2

SPGO	63	4.2
SPGO	65	4.2
SPGO	70	4.2
SPGO	75	4.2
SPGO	80	4.2
SPGO	40	6.3
SPGO	45	6.3
SPGO	50	6.3
SPGO	55	6.3
SPGO	60	6.3
SPGO	63	6.3
SPGO	65	6.3
SPGO	70	6.3
SPGO	75	6.3
SPGO	80	6.3
SPGO	85	6.3
SPGO	90	6.3
SPGO	95	6.3
SPGO	100	6.3
SPGO	105	6.3
SPGO	110	6.3
SPGO	115	6.3
SPGO	120	6.3
SPGO	125	6.3
SPGO	130	6.3
SPGO	135	6.3
SPGO	140	6.3
SPGO	150	6.3
SPGO	160	6.3
SPGO	180	6.3
SPGO	80	8.1
SPGO	85	8.1
SPGO	90	8.1
SPGO	95	8.1
SPGO	100	8.1
SPGO	105	8.1
SPGO	110	8.1
SPGO	115	8.1
SPGO	120	8.1
SPGO	125	8.1
SPGO	130	8.1

SPGO	135	8.1
SPGO	140	8.1
SPGO	145	8.1
SPGO	150	8.1
SPGO	155	8.1
SPGO	160	8.1
SPGO	165	8.1
SPGO	170	8.1
SPGO	175	8.1
SPGO	180	8.1
SPGO	185	8.1
SPGO	190	8.1
SPGO	200	8.1
SPGO	210	8.1
SPGO	220	8.1
SPGO	225	8.1
SPGO	230	8.1
SPGO	240	8.1
SPGO	250	8.1
SPGO	260	8.1
SPGO	270	8.1
SPGO	280	8.1
SPGO	290	8.1
SPGO	300	8.1
SPGO	310	8.1
SPGO	315	8.1
SPGO	320	8.1
SPGO	330	8.1
SPGO	340	8.1
SPGO	350	8.1
SPGO	360	8.1
SPGO	140	9.7
SPGO	150	9.7
SPGO	160	9.7
SPGO	170	9.7
SPGO	180	9.7
SPGO	100	7.2
SPGO	110	7.2
SPGO	120	7.2
SPGO	130	7.2

Product link : <https://www.jspseal.com/ptfe-piston-seal-jspgo.html>